

Artikel-Nr.	Hubkra ft in t	Hub (H) in mm	Abmessungen in mm										Gew icht in kg
			A	C	C1	C2	C3	D	D1	E	E1	K	

Schleusenwinde mit Sicherheitskurbel (Siku)

140.015-0800.01	1,5	800	1150	260	200	132	91	18	13	50	130	250	14
140.030-0800.01	3	800	1260	260	200	147	97	22	17	50	130	250	24
140.050-0800.01	5	800	1280	290	220	158	108	22	18	50	130	250	32
140.100-0800.01	10	800	1405	400	320	190	130	25	21	65	250	300	53

Schleusenwinde mit Sicherheits-Ratschenkurbel (Raku)

240.015-0800.01	1,5	800	1150	260	200	132	91	18	13	50	130	250	14
240.030-0800.01	3	800	1260	260	200	147	97	22	17	50	130	250	24
240.050-0800.01	5	800	1280	290	220	158	108	22	18	50	130	250	32
240.100-0800.01	10	800	1405	400	320	190	130	25	21	65	250	300	53

Schleusenwinde mit Druckrollen-Sicherheitskurbel (DSK)

340.015-0800.01	1,5	800	1150	260	200	132	91	18	13	50	130	250	14
340.030-0800.01	3	800	1260	260	200	147	97	22	17	50	130	250	24
340.050-0800.01	5	800	1280	290	220	158	108	22	18	50	130	250	32

SLUISLIEREN

